

## Benchmark Hotplates, Stirrers and Hotplate Stirrers

### Product Highlights

- ✓ Exceptionally durable, chemical resistant white ceramic work surface
- ✓ Space-efficient design (8 x 9 in. footprint). Ideal for use on crowded benchtops and inside of bio-hoods
- ✓ Precise adjustments and maintenance of speed and temperature
- ✓ Compatible with borosilicate glass beakers, flasks, bottles and other vessels
- ✓ Advanced microprocessor controls with convenient turn knobs
- ✓ Safety indicator LED
- ✓ 2-Year Warranty
- ✓ CE

### Specifications:

#### Hotplate (H4000-H / H4000-H-E)

- Temperature Range: Amb. +5 to 380 °C
- Platform: 7.5 x 7.5 in. (190.5 x 190.5 mm)
- Control: Quick Adjustment Knob
- Dimensions: 8 x 9 x 4.5 in. (203.2 x 228.6 x 114.3 mm)
- Power: 400 watts
- Available in 120V (60 Hz) or 230V (50/60Hz)

#### Magnetic Stirrer (H4000-S / H4000-S-E)

- Speed Range: 60 to 1500 rpm
- Platform: 7.5 x 7.5 in. (190.5 x 190.5 mm)
- Dimensions: 8 x 9 x 4.5 in. (203.2 x 228.6 x 114.3 mm)
- Power: 300 watts
- Available in 120V (60 Hz) or 230V (50/60Hz)

#### Hotplate Magnetic Stirrer (H4000-HS / H4000-HS-E)

- Temperature Range: Amb. +5 to 380 °C
- Speed Range: 60 to 1500 rpm
- Platform: 7.5 x 7.5 in. (190.5 x 190.5 mm)
- Dimensions: 8 x 9 x 4.5 in. (203.2 x 228.6 x 114.3 mm)
- Power: 500 watts
- Available in 120V (60 Hz) or 230V (50/60Hz)
- Comes complete with a support rod to mount thermometers and temperature probes

### Accessories

Part Number	Description
H4000-ROD	Replacement Support Rod for Hotplate Magnetic Stirrer



### Ordering Information

Part Number	Description
H4000-H	Hotplate, 120V, Standard 3-prong (NEMA 5-15) plug
H4000-H-E	Hotplate, 230V, Standard 2-pin European (Type C) plug
H4000-S	Magnetic Stirrer, 120V, Standard 3-prong (NEMA 5-15) plug
H4000-S-E	Magnetic Stirrer, 230V, Standard 2-pin European (Type C) plug
H4000-HS	Hotplate Magnetic Stirrer, 120V, Standard 3-prong (NEMA 5-15) plug
H4000-HS-E	Hotplate Magnetic Stirrer, 230V, Standard 2-pin European (Type C) plug